



Founded in 2003, Aria Telecom Solutions (P) Ltd. has grown to become a leader in the voice processing industry, now located in New Delhi.

ARIA TVRS is No 1 Voice Logger brand in India & one of the best in the World

ARIA is committed to provide latest & stable technology to our clients in cost effective price.

In the same line we have come up with new series of PRI Voice Logger with PCI Express connectivity.

ARIA TVRS has Web based GUI for live monitoring & complex search options.



**ISO 9001:2008**  
Certified Company

### Award & Recognitions

- Leaders in CTI Solutions Award – Business Sphere
- Technology Excellence Award – Leaders in IVR -2013
- Global Business & Services Award – Leader in Customized Telecom Solution 2013
- ISO 9001:2008 Certified Company
- Registered with MSME (Micro, Small & Medium Enterprise)
- Registered with NSIC (National Small Industries Corporation of India)
- Trust Seal Certified Company



### **ARIA AK16-16 PORT LOGGER**

ARIA-AK16 is Sixteen Channel embedded Telephone Recording System with HDD to save voice files. Also has LAN Port connectivity to connect with computer, it can be used with direct telephone lines, EPABX extensions, VOIP FXS/ FXO, Wireless Radio equipment etc

- No need Computer
- Inbuilt speaker, mike & Display to search & listen recording file
- Parallel Connectivity
- Compatible with GSM / CDMA FCT
- Answering machine to leave message in case of no answer
- Auto answer & record facility
- SD card support up to 32 GB

## ARIA AK16 Specifications:

Simultaneously recording channels	8,16, 24,32
Recording interface	RJ-11
Available hard disk capacity	500GB, 1TB&2TB are selectable
Displayer	Touch Screen 5'' TFT
Maximum Recording Time	>140,000H
Start recording mode	timing, reversed polarity, keying, Voice Activated
Off hook detect voltage	<(3-80)V
On hook detect voltage	>(10-100)V
CID detected signal	DTMF/FSK
CID detect intensity range	0 dB to -32dB
Affected Frequency range	100 Hz to 3400 Hz
Input impedance	AC: 100K, DC: 5.1M
Signal-to-crosstalk ratio	> 60 dB
S/N ratio	> 70 dB
Input voltage	DC19V
Input voltage range	DC18V-DC24V
Operating current	1.5A
Maximum current	3A
Rating power consumption	10W
Battery type	2*12V/2C lead-acid batteries in series
Operating Temperature	0°C to 40°C
Operating Humidity	10% to 90 %
Network interface	RJ-45
Accessories	DC19v power adapter, software, User Manual, DB37*2 RS232
Dimension(L*W*H) CM	43*39*9cm
Packing dimension(L*W*H) CM	55*48*15cm
Net weight	6.6kg
Gross weight	9.1kg

## Some Important Clients

